

DESCRIPTION

The Model A-ML is an omni-directional, low impedance, electret condenser microphone with mic level audio. It is housed in a high impact ABS dome designed for ceiling or wall mounting. Normal pick-up pattern is approximately 15' from the microphone location, all directions, or within 30' diameter circle. It is used for cameras with mic level audio input.

APPLICATION

The Model A-ML Microphones can be used in situations such as:

- Convenience Stores
- Fast Food Restaurants
- Booking Rooms
- Interrogation Rooms
- Day Care Centers
- Sleep Disorder Centers
- Therapy Labs
- Cashier Booths
- Gas Stations
- Anywhere CCTV Cameras Are Installed

MODEL A-ML MICROPHONE




FEATURES

- Sturdy ABS housing
- Microphone can pick up normal sounds 15' away
- Easy surface mount to wall or ceiling
- May be located up to 20' from IP Camera or pre-amp.

SPECIFICATIONS

▪ Sensitivity	-45 dB/pa
▪ Frequency response	50 Hz to 8 kHz
▪ Output Impedance	1kΩ
▪ Current drain	0.8mA
▪ Supply voltage	1.8Vdc to 4.5Vdc
▪ Microphone housing	High impact ABS
▪ Dimensions	4" dia x 1 ½" H
▪ Weight	7.5 oz
▪ Weight	1 lb

IMPORTANT NOTICE
 When this equipment is used as part of an audio monitoring system, the law requires that the public be given notice of AUDIO MONITORING ON THE PREMISES. A decal notice is included with each microphone shipped.



Federal Law References:
 Federal Regulations, US Code, Title 18.
 Crime and Criminal Procedure, Sec.2510.

