



4MP Flexible Intensifier® HD-TVI Bullet Camera with Junction Box, Dual Voltage

H4FB2M

2.7 - 12mm motorized zoom focus lens, dark gray housing

Features

- Flexible Intensifier Technology® fits any lighting application
- Supports 4MP @ 30FPS
- True WDR operation
- Adaptive IR LED's
- Presets: Outdoor, Low Light, Hallway, Lobby, Elevator, Indoor
- Built-in heater and anti-fog glass reduces condensation
- 3-axis for wall and ceiling mounting
- Full OSD and Zoom / Focus control through on-board and UTC
- Signal distance up to 1600 feet*
- Vandal / tamper resistant
- IP67 compliant, weather resistant
- 12VDC & 24VAC dual voltage operation
- 5 year warranty



Camera Specifications

Image Sensor	1/2.8" SONY Starvis 6MP Sensor
Minimum Illumination	0.00 lux (IR LED 'on')
Effective Pixels	2616 (H) x 1964 (V)
Total Pixels	2704 (H) x 2104 (V)
Scanning System	Progressive
S/N Ratio	More than 50dB
Video Output	1.0Vp-p / 75 Ohms
Electronic Shutter	Auto / Manual (1/30 - 1/30,000 sec.)
WDR	On (Low / Middle / High) / Off
Day / Night	Auto / Intensifier
Test Monitor Output	TVI out
Power	12VDC / 24VAC
Power Consumption	900mA max. (DC), 700mA max. (AC)
Operating Temperature	-40° F - 140° F
Unit Dimensions	9.64" (L) x 3.72" (Dia.)
Unit Weight	2 lbs (camera), 0.9 lbs (junction box)
Certifications	FCC, RoHS

*with compatible Speco recorder

**Products are in compliance with NDAA Section 889 Part B Guidelines

Optional Accessories



PSW5
12VDC
Power Supply



PSW4
24VAC 50VA
Power Supply



INTCM1
Corner Mount



Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 4/5/24

800-645-5516 • Fax: 631-957-9142 or 631-957-3880 • www.specotech.com

