



HAC335-MD



FEATURES

IVMS 3MP HD-TVI Exterior IR Turret Camera

- 3MP Video Output
- HDTVI Technology
- OSD menu, 3D DNR, Smart IR
- 60 ft IR distance
- IP66 weatherproof
- Up the Coax (control over coax)
- True WDR

| Specifications | |
|-------------------|---|
| Model Number | HAC335-MD |
| Image Sensor | 3MP CMOS |
| Video Format | PAL / NTSC |
| Effective Pixels | 2052(H)*1536(V) |
| Min. Illumination | 0.01 Lux @ (F1.2, AGC ON), 0 Lux with IR |
| Shutter Time | 1/30s to 1/50,000 s |
| Lens | 3.6mm (2.8mm, 6mm optional), Angle of View: 80.9°(3.6mm), 103.5°(2.8mm), 54.3°(6mm) |
| Angle Adjustment | Pan: 0 - 360°, Tilt: 0 - 75°, Rotation: 0 - 360° |
| Day & Night | ICR |
| Video Frame Rate | 2052*1536 @ 18fps |
| HD Video Output | 1 HD-TVI output |
| CVBS Output | N/A |

| Specifications | |
|--------------------------------|---|
| D/N Mode | Color / BW / Smart |
| Functions | WDR, DNR, Mirror, Smart IR |
| WDR | 120dB True WDR |
| Working Temperature / Humidity | -40 °C - 60 °C (-40 °F - 140 °F) Humidity 90% or less (non-condensing) |
| Power Supply | 12 VDC±10% |
| Power Consumption | Max. 5W |
| Weather Proof Ratings | IP66 |
| IR Range | Up to 60 ft |
| Communication | OSD (UTC Control) via DVR |
| Dimensions | 89.6 × 59.1 mm (3.53" × 2.33") |
| Weight | 400 g (0.88 lb) |
| Electrical Box | HTH-280ZJ-XS |
| Wall Mount | HTH-272ZJ-110B-TRS |
| Pole Mount | HTH-275ZJ |
| Corner Mount | HTH-276ZJ |