

# HNC328G2-TDB



## FEATURES

8MP True WDR Fixed Mini Dome, Exterior, Grey Housing

- Grey Housing
- 8 Megapixel (3840 x 2160) Resolution
- Full HD 5MP real-time video
- 3D DNR, True WDR, BLC
- IP67 & IK10 Rating
- PoE
- Vandal-proof

Specifications	
Model Number	HNC328G2-TDB/2.8
Image Sensor	1/2.8" Progressive Scan CMOS
Min. illumination	0.005 Lux @ (F1.6, AGC ON), B/W: 0 Lux with IR
Shutter time	1/3s ~ 1/100,000s
Lens	Fixed focal length, 2.8
Angle adjustment	Pan: -90° ~ 90°, tilt 0° ~ 75°, Rotation: 0-355°
Digital noise reduction	3D DNR
Wide dynamic range	True WDR
Day & night	ICR
Video compression	Main stream: H.265/H.264/H.264+/H.265+ Sub-stream: H.265/H.264/MJPEG
Dual stream	Yes
Max. image resolution	3840×2160

Specifications	
Frame rate	60 Hz: 20 fps (3840 × 2160) 30 fps (3200 × 1800, 2688 × 1520, 1920 × 1080, 1280 × 720)
Image settings	Saturation, brightness, contrast, sharpness adjustable through client software or web browser
BLC	Yes, zone configurable
On Board Storage	Micro SD slot, up to 128GB
Network Storage	Support microSD/SDHC/SDXC card (128G) local storage, NAS (NFS,SMB/CIFS), ANR
Alarm trigger	Motion detection, tampering alarm
Protocols	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP, RTSP, PPPoE, SMTP, NTP, SNMP, HTTPS, FTP, 802.1x, Qos
System compatibility	ONVIF, PSIA, CGI
General functionalities	User authentication, watermark
Communication interface	1 RJ45 10M / 100M Ethernet interface
Operating conditions	-30°C ~ 60°C (-22°F ~ 140°F) humidity 90% or less (non-condensing)
Power supply	12 VDC +/- 25%, PoE (802.3af)
Power consumption	Max, 7.5W
Ratings	IP67 / IK10
IR range	Up to 90ft
Dimensions	Ø 110.8 mm × 84.7 mm (Ø 4.4" × 3.3")
Weight	520g (1.1 lbs)
Electrical Box	HTH-280ZJ-DM18G
Wall Mount	HTH-272ZJ-110BG