

HNC61C-VBA



FEATURES

12MP Motorized IR EXIR Bullet, Exterior

- 1/1.7" Progressive Scan CMOS
- Up to 12 Megapixel (4000 × 3000) High Resolution
- 8MP Real-time Video
- Day / Night
- Audio 1/1 and Alarm 1/1
- Vandal-proof Housing
- Motorized VF Lens

Specifications	
Model Number	HNC61C-VBA
Image Sensor	1/1.7" progressive scan CMOS
Min. illumination	0.008 lux@F1.2, AGC ON, 0 lux with IR
Shutter time	1s ~ 1/100,000s
Lens	Motorized VF lens, 2.8 ~ 12 mm @F1.4, angle of view: 101° ~ 36.1°
Angle adjustment	Pan: 0° ~ 355°, Tilt 0° ~ 90°, Rotation 0 ~ 360°
Day & night	IR Cut filter with auto switch
Wide Dynamic Range	DWDR
Video compression	H.264 / H.264+ / H.265 / H.265+ / MJPEG
Bit rate	32 Kbps ~ 16 Mbps
Max, image resolution	12MP CMOS, (4000 × 3000)
Frame rate	20fps, (4000 x 3000), 30fps (3840 × 2160)
Network storage	NAS
System compatibility	ONVIF, ISAPI, SDK
Communication interface	1 RJ45 10M / 100M Ethernet port and 1 RS-485 interface
Video output	1 Vp-p composite output (75 Ω / RCA)
On-board storage	Built-in SD slot, up to 128 GB
Reset button	Yes

Specifications	
Operating conditions	-30 °C ~ 65 °C (-22 °F ~ 149 °F) humidity 95% or less (non-condensing)
Power supply	DC 12V, PoE (802.3at, class 4)
Power consumption	13W
Protection	IK10, IP67
IR range	150 feet
Dimensions	Ø 5.7" x 13.7"
Weight	2100g (5.4 lbs)
Corner and Pole	C:HTH-276ZJ, P:HTH-275ZJ