

# **2MP HD-TVI IR Bullet Camera** with Included Junction Box

## **HT7040TM**

2.8-12mm motorized lens, dark gray housing









## **Features**

- Full HD resolution over coax (HD-TVI)
- Supports up to Full HD 1080p @ 30fps
- True WDR operation
- Intense IR function no saturation, IR intensity adapts to subject to provide vivid image
- True day/night operation mechanical IR cut filter
- Built-in heater and anti-fog glass reduces condensation
- Full OSD operation through on-board control and UTC (up the coax)
- Additional 960H analog output
- Signal distance up to 1600 feet\*
- 12VDC & 24VAC dual voltage operation
- Vandal resistant
- IP67 compliant, weather resistant
- 5 year warranty







1/3" 2MP Sensor
1984 (H) x 1105 (V)
2000 (H) x 1121 (V)
1920x1080 @ 30fps / 1280x720 @ 60fps
0.001 lux (sense-up x32)
Progressive
1.0Vp-p / 75 Ohms
More than 50dB
0-10 level adjustable
Auto / Manual (1/30 – 1/30,000 sec.)
On (Low / Middle / High) / Off
Color / BW / Auto / Ext
0-20 level adjustable
2x – 32x (adjustable)
On / Off (4 zones)
On / Off (16 zones)
Auto / Auto Ext / AWC - SET / Manual
On / Off
On / Off
0-10 level adjustable
Off / Low / Middle / High

Operating & Unit Specifications	
Power Supply	12VDC / 24VAC dual voltage (power supply not included)
Power Consumption	12VDC, 800mA max. / 24VAC, 290mA max.
Operating Temperature	-4°F - 122°F
Unit Dimensions	9.65" (L) x 3.74" (H)
Unit Weight	3 lbs.



ts are in compliance with NDAA Section 889 Part B Guidelines

### **Optional Accessories**



Test Monitor Output Communication





PSW5 12VDC **Power Supply** 



PSW4 24VAC **Power Supply** 

<sup>\*</sup>Signal distance up to 1000 depending on coax quality. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 10/3/22



UTC (up the coax)