



Multi-Format HD Miniature Pinhole Camera

HT7PHT

3.7mm pinhole lens

Features

- Full HD 1080p @ 30FPS
- Multi-format HD
- Full OSD control via UTC (up the coax)
- Perfect for covert applications
- 12VDC operation (power supply not included)
- 5 year warranty



Specifications

Image Sensor	1/2.9" 2MP CMOS
Resolution	1920 x 1080
Minimum Illumination	0.001 lux
Scanning System	Progressive
S/N Ratio	More than 52dB
Video Output	HD-TVI / HD-AHD / HD-CVI / CVBS
Signal System	NTSC / PAL
OSD	Available (UTC)
3D/2D	On
Sense-up	On
Smart IR	On
Back Light Compensation	Off
White Balance	Auto
Type	Color

Operating & Unit Specifications

Power Supply	DC12V ± 10%
Power Consumption	95mA max.
Dimensions	1.77" (H) x 1.5" (W) x 0.98" (L)
Weight	2.47oz
Storage Temperature	-22° F - 140° F
Operating Temperature	-22° F + 113° F

Optional Accessories



PSW5
12VDC
Power Supply



O5E1*
IP Encoder
*converts analog to
Speco Blue IP camera

NDAA
COMPLIANT

*Products are in compliance with NDAA Section 889 Part B Guidelines

Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 1/3/24

800-645-5516 • Fax: 631-957-9142 or 631-957-3880 • www.specotech.com

