

# **4K HD-TVI Vandal Dome Camera** with Junction Box

## HTD8TG

2.8mm fixed lens, dark gray housing







### **Features**

- Supports up to 8MP@15fps
- Built-in high powered IR LEDs
- Digital WDR (wide dynamic range) operation
- IP66 compliant, weather resistant
- 12VDC (power supply not included)
- Junction box included for convenience
- 5 year warranty







Camera Specifications	
Max Aperature	F=1.6
Focal Control	Manual
Image Sensor	Progressive Scan, 1/2.0" CMOS Sensor, 8MP
Effective Pixels	3840(H)x2160(V)
Maximum Resolution	3864x2176
Minimum Illumination	0.1 lux
White Balance	AWB/ATW/AWC
WDR	DWDR/OFF/AUTO
Day/Night	IR Cut Filter/Auto/Color/B&W/EXT
DNR	2D-DNR/3D-DNR (Low/Middle/High)
Output	TVI
S/N Ratio	52dB (AGC OFF)
Frame Rate	8MP @ 15fps

Video Specifications	
Main Resolution	3840x2160 @15fps
TV System	NTSC
Brightness	1 ~ 100
Motion	ON/OFF
Shutter	AUTO/FLK
Mirror/Flip	OFF/MIRROR
Color Gain	Blue Gain/Red Gain (1 ~ 10)
AGC (Auto Gain Control)	0 ~ 15
IR Distance	6pcs Super LEDs (66ft)
Remote Control Interface	UTC

Operating & Unit Specifications		
Power	12VDC (power supply not included)	
Power Consumption	Max. 5W	
Operating Temperature	14°F ~ 122°F	
Unit Weight	0.7 lbs	

\*Products are in compliance with NDAA Section 889 Part B Guidelines

### **Optional Accessories**



PSW5 12VDC Power Supply



**TVIUTPPT** HD Video Transceiver with Pigtail (Balun)



**TVIUTP** HD Video Transceiver

Store is a service mark of Apple Inc. Android, Google Play and the Google Play logo are trademarks of Google Inc. Speco Technologies is constantly developing and improving products. We reserve the right to modify product design and specifications without notice and without incurring any obligation. Spec Rev. 7/27/23







