



# 1000TVL Intensifier® Dome Camera

## HTINT59K1

2.8-12mm varifocal lens, dark gray housing

### Features

- 1/3" 1.3MP Sensor
- 1000 TV lines highest resolution in analog
- Superior low-light performance
- True WDR operation
- Amplify existing light with no distance limitation
- Built-in heater and anti-fog glass reduces condensation
- Presets: Indoor, Outdoor, Low Light, Lobby, Elevator
- 3-axis for lens mount
- Full OSD operation through on-board control
- Chameleon Cover™: snaps on and can be painted to match any décor!\*
- Vandal / tamper resistant
- IP67 compliant, weather resistant
- 12VDC & 24VAC dual voltage operation
- 5 year warranty
- NDAA Compliant\*



Shown with included paintable, snap-on Chameleon Cover™




### Camera Specifications

Image Sensor	1/3" CMOS, 1.3MP
Minimum Illumination	0.0001 lux (sense-up x32)
Effective Pixels	1305 (H) x 1049 (V)
Total Pixels	1312 (H) x 1069 (V)
Scanning System	Progressive
S/N Ratio	More than 50dB
Output Resolution	1000TVL
Video Output	1.0Vp-p / 75 Ohms
Electronic Shutter	Auto/Manual (1/60 - 1/60,000 sec.)
WDR	On (Low/Middle/High)/Off
Day/Night	Auto/Color/BW/External
White Balance	Auto/AWB/AWC-Set/Manual
Brightness	0 - 20 (adjustable)
AGC	0 -10 (adjustable)
Sense-up	2x - 32x (adjustable)
Backlight	BLC/HLC
Motion Detection	On/Off (4 zones)
Privacy Masking	On/Off (16 zones)
Mirror	On/Off
Flip	On/Off
Sharpness	0 - 10 (adjustable)
DNR	Off/Low/Middle/High


### Operating & Unit Specifications

Power	12VDC/24VAC dual voltage <b>(power supply not included)</b>
Power Consumption	12VDC, 500mA max. 24VAC, 195mA max.
Operating Temperature	-4°F - 122°F
Unit Dimensions	3.95" (H) x 5.24" (Dia)
Unit Weight	3 lbs.
Certifications	FCC, RoHS


#### Optional Accessories



**PSW5**  
12VDC  
Power Supply



**INTWM1**  
Wall Mount  
(use with  
Junction Box)



**INTCM1**  
Corner Mount  
(use with INTWM1)

\*Products are in compliance with NDAA Section 889 Part B Guidelines

