

# N2 x 4MP Network LumiDeterrent Stitched Turret Camera (2.8 mm)

N5P-8DA2



## Key Features

- 2 x 4MP Turret Housing
- 180° Stitched Multi-Sensor
- 2.8 mm Lens
- LumiLuxSmart With IR and White-Light LEDs
- LumiDeterrent With Red/Blue Lights and Built-In Speaker
- Video Content Analytics: Line Crossing and Intrusion
- iMD, LumiSearch, LumiTracking

## Certifications and Compliance

- NDAA Compliant
- FCC
- IC
- UL

## Learn More



Learn more about this camera's key technologies.



View all compatible accessories for this camera.

## Overview

The **N5P-8DA2** is part of Luminy's N5 mainstream series of security devices. N5 mainstream series devices are designed with a suite of advanced LumiTechnologies to meet the needs of today's evolving security market.

## Key Technologies

**LumiDeterrent** technology integrates full-color video, active deterrence, and AI algorithms to provide 24/7 security. This technology can accurately identify potential risks and prevent incidents with red and blue light alarms and enhanced sound alarms.

**LumiLuxSmart** technology allows cameras to capture clear, full-color video day or night. When motion is detected, LumiLuxSmart cameras switch from IR LEDs to white-light LEDs to illuminate a scene, then switch back to IR mode once motion has ceased to prevent light pollution and energy inefficiency.

**LumiSearch** technology lets you quickly find, track, and identify targets in security footage using a reference image. The LumiSearch+ algorithm analyzes human body shape, clothing color, and other characteristics to accurately pinpoint where a target has appeared in footage captured by any LumiSearch+-enabled camera and NVR.

**LumiTracking** technology enhances security and efficiency by automating tracking of people and vehicles. It uses advanced AI algorithms to monitor and predict the direction and speed of moving targets, enabling quick response to potential issues for enhanced security and smooth operation.

# Specifications

## Camera

Luminys Series	N5 Series (Mainstream)
Image Sensor	1/2.7-in. 4MP Progressive CMOS
Maximum Resolution	4096 × 1860
Minimum Illumination	<b>Color:</b> 0.002 Lux at F1.4 <b>Black/White:</b> 0.0002 Lux at F1.4 0 Lux With IR Light On
Number of Illuminators	<b>IR:</b> Two (2) <b>White Light:</b> Two (2)
Illuminator Control	Automatic, Manual
Maximum Illumination Distance	<b>IR:</b> Up to 25.0 m (82.0 ft) <b>White Light:</b> Up to 20.0 m (66.0 ft)
Electronic Shutter Speed	Automatic, Manual 1/3 s to 1/100,000 s
Pan/Tilt/Zoom	<b>Pan:</b> 0° to 360° <b>Tilt:</b> 0° to 77° <b>Zoom:</b> 0° to 360°
S/N Ratio	> 56 dB

## Lens

Iris Type	Fixed
Lens Type	Fixed
Focal Length	2.8 mm
Maximum Aperature	F1.4
Field of View	<b>Horizontal:</b> 180° <b>Vertical:</b> 86°
Close Focus Range`	0.8 m (2.6 ft)
DORI Distance	<b>Detect:</b> 50.6 m (166.0 ft) <b>Observe:</b> 20.2 m (66.3 ft) <b>Recognize:</b> 10.1 m (33.1 ft) <b>Identify:</b> 5.1 m (16.7 ft)

## Video

Compression	LumiFocus, H.265, H.264, H.264H, H.264B, MJPEG (Sub Stream Only)
Stream Capability	Three (3) Streams
Resolution	8MP (4096 × 1860), 6MP (3632 × 1632), 4MP (3040 × 1368), 1.6MP (1920 × 860), 1200 × 530, 960 × 432
Maximum Frame Rate	<b>Main Stream:</b> 4096 × 1860 at 1–20 fps <b>Sub Stream 1:</b> 1200 × 530 at 1–20 fps <b>Sub Stream 2:</b> 1920 × 1080 at 1–20 fps
Video Bit Rate	<b>H.264:</b> 6 to 16384 kbps <b>H.265:</b> 6 to 16384 kbps
Bit Rate Control	CBR/VBR
Day/Night	Automatic (ICR), Color, Black and White
Light Balancing	Wide Dynamic Range (120 dB)
Noise Reduction	3D NR
Defog	Supported
Region of Interest	Four (4) Zones
Privacy Masking	Four (4) Zones

## Analytics

Video Content Analytics	Line Crossing, Intrusion, Loitering Detection
-------------------------	---

## Analytics

Intelligent Motion Detection	Supported With Alarms for Vehicles and Humans
LumiSearch	Supported When Used With LumiSearch-Enabled NVRs
LumiTracking	Zoom and Track Multiple Humans/Vehicles and Trigger Alarms Automatically

## Audio

Compression	PCM, G.711a, G.711Mu, G.726, G.723
Interface	<b>Input:</b> Built-in Dual Microphones and One (1) RCA Port <b>Output:</b> Built-in Speaker and One (1) RCA Port

## Alarm

Event	No SD Card, SD Card Full, SD Card Error, Network Disconnection, IP Conflict, Illegal Access, Motion Detection, Video Tampering, Voltage Detection, Security Exception, Line Crossing, Intrusion, Scene Changing, Audio Detection, External Alarm, iMD
Interface	<b>Input:</b> One (1) Channel (3V-5VDC, 5 mA) <b>Output:</b> One (1) Channel (12 VDC, 300 mA)

## Network

Protocol	RJ-45 (10/100 Base-T)
Protocol	IPv4, IPv6, HTTP, HTTPS, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP; NTP, Multicast, ICMP, IGMP, NFS, PPPoE, 802.1x
Interoperability	ONVIF (Profile S/G/T), API, SDK
Browser	Chrome, Firefox
Client	LumiViewer, LumiViewer Mobile App
Storage	FTP, SFTP, NAS, Micro SD Card (Max. 256 GB)

## Electrical

Power Supply	12 VDC/PoE (802.3af)
Power Consumption	<b>12 VDC</b> <ul style="list-style-type: none"><li>• <b>Maximum:</b> 8.7 W</li><li>• <b>Normal:</b> 4.0 W</li></ul> <b>PoE</b> <ul style="list-style-type: none"><li>• <b>Maximum:</b> 10.9 W</li><li>• <b>Normal:</b> 5.0 W</li></ul>

## Construction

Net Weight	1.0 kg (2.2 lb)
Gross Weight	1.3 kg (2.8 lb)
Operating Temperature	-40 to 60 °C (-40 to 140 °F) < 95% RH (Non-Condensing)
Storage Temperature	-40 to 60 °C (-40 to 140 °F)
Protection Ratings	IP67
Dimensions	140.6 mm × Φ 142.5 mm (5.5 in. × Φ 5.6 in.)
Material	Metal

## Certifications and Compliance

Certifications	FCC, UL, IC
Compliance	NDAA

## Dimensional Drawing

mm [in.]

