

NVR401L-4P4

4 Channel 1U 1HDD 4POE Network Video Recorders



Key Features

- 4CH IP video input, up to 8MP
- H.265+/H.265 dual-stream video compression
- Incoming/Outgoing bandwidth: 40Mbps/80Mbps
- Decoding: 6CH 1080P@30fps/3CH 4MP@30fps/2CH 5MP@30fps/2CH 6MP@30fps/1CH 8MP@30fps
- Supports mainstream cameras of ONVIF and RTSP protocol
- VGA/HDMI simultaneous video output, maximum resolution of HDMI is 4K
- AI by camera: SMD, perimeter protection, face detection, etc.



Professional and Reliability

- H.265+ compression effectively reduces storage requirements by up to 75%
- Third-party cloud storage integration -Google Drive and Dropbox for video backup

Stability

- Automatic network replenishment

Third-Party Compatibility

- Supports ONVIF and RTSP protocols for seamless integration with third-party cameras

Smart search and playback

- Smart search and smart playback for the smart events triggered by humans or vehicles

HD Video Output

- Provide simultaneous HDMI and VGA outputs

- HDMI video output at up to 4K resolution

Storage and Playback

- 1 SATA interfaces (up to 14 TB capacity per HDD)
- 4-ch synchronous playback

Network & Ethernet Access


- 4 independent PoE network interfaces supported long distance transmit
- 1 self-adaptive 10/100Mbps Ethernet interface
- Homaxi-view for easy network management

Specification


| Video & Audio Input | |
|----------------------|--|
| IP Video Input | 4 ch |
| Audio Input | 1 ch, RCA |
| Video & Audio Output | |
| HDMI | 1 ch, resolution:4K(3840 × 2160)/30 Hz,1920 × 1080/60 Hz,1280 × 1024/60 Hz,1280 × 720/60 Hz |
| VGA | 1 ch, resolution:1920 × 1080/60Hz,1280 × 1024/60 Hz,1280 × 720/60 Hz |
| Audio Output | 1 ch, RCA |
| Recording | |
| Compression | H.265+/H.265/H.264+/H.264 |
| Resolution | 8MP/5MP/4MP/3MP/1080P/720P/D1/CIF/QCIF |
| Bit Rate | 64 Kbps ~ 10 Mbps |
| Playback & Backup | |
| Playback Resolution | 8MP/5MP/4MP/3MP/1080P/720P/D1/CIF/QCIF |
| Decoding Capability | 1 ch @ 8M 30fps 2 ch @ 6M 30fps 2 ch @ 5M 30fps 3 ch @ 4M 30fps 6 ch @ 1080P 30fps |
| Synchronous Playback | 4 ch |
| Playback Mode | Smart Playback/Normal/Time Division/Label/Event/Log playback |
| Backup Mode | USB Device/Network |
| Advanced Features | |

| | |
|---------------------------|---|
| Smart Detection By Camera | Area Intrusion, Line crossing, Region Entrance /Region Exiting, Fast Moving, Object Missing, Unattended Object, Loitering Detection, Parking Detection, Face Detection, People Gathering Detection, Blurred detection, Scene change detection, Audio exception detection, Human Detection, Vehicle Detection, SMD, PP |
| Smart Playback | Face detection/Line Crossing/Are Intrusion/Motion Detection/Human Detection/Vehicle Detection |
| Cloud Storage | Support |
| Cloud Upgrade | Support |
| Network | |
| Incoming Bandwidth | 40 Mbps |
| Outgoing Bandwidth | 80 Mbps |
| Ethernet | 1 RJ-45 10/100 Mbps self-adaptive Ethernet interface |
| Protocols | HTTPs, HTTP, TCP/IP, IPv4, UPnP, RTSP, UDP, SMTP, SNMP, NTP, DHCP, DNS, IP Filter, DDNS, FTP, P2P, ONVIF |
| Mobile Surveillance | IOS, Android |
| Hard Disk | |
| SATA | 1 SATA interface |
| Capacity | Up to 14TB capacity for each HDD |
| External Interface | |
| POE Interface | 4 independent 10/100 Mbps PoE Ethernet interfaces |
| USB Interface | Front panel: 1 × USB 2.0 Rear panel: 1 × USB 2.0 |
| Alarm In | N/A |
| Alarm Out | N/A |
| General | |
| Operating Conditions | (-10°C ~ 55°C) (14°F ~ 131°F) Humidity 10% ~ 90% (non-condensing) |
| Power Supply | MAX.10 W (without HDD and POE) |
| Power Consumption | DC 48 V, 1.36 A |
| Dimensions (W × D × H) | 9.84" × 9.05" × 1.77", 1U (250 × 230 × 45 mm) |
| Gross Weight | 3.31 lb (1.5 kg) |

Dimensions



Rear Panel



| No. | Description | No. | Description |
|-----|------------------|-----|------------------|
| 1 | Power Switch | 6 | Audio IN/OUT RCA |
| 2 | Power Input | 7 | USB Port |
| 3 | POE Network Port | 8 | Network Port |
| 4 | VGA Port | 9 | Ground |
| 5 | HDMI Port | | |