



8MP IP Dome Camera with Line Crossing and Intrusion Detection with Junction Box, NDAA Compliant

O8VD3M

2.8-12mm motorized lens, white housing

Features

- Captures up to 8MP @ 20fps
- Built-in standard PoE (IEEE 802.3af)
- True Day/Night operation (IR cut filter)
- IR range: up to 165' (depending on scene reflection)
- True WDR
- Micro SD card slot up to 256GB (card not included)
- Conformant with ONVIF Profile G/S/T
- Built-in mic
- Line crossing, region intrusion and scene change detection*
- IP67 Weather Resistance
- IK10 Vandal Resistance
- Junction Box Included
- 5 year warranty



Camera Specifications

| | |
|--------------------------|---|
| Image Sensor | Progressive scan 1/2.8" CMOS, 8MP |
| Maximum Resolution | 3840 x 2160 (8MP) |
| Field of View | 99°-34°(H); 53°-18°(V); 115°-36°(D) |
| Minimum Illumination | 0.02 lux @ F1.6, AGC ON, 0 lux with IR |
| Day/Night | Smart IR |
| Compensation | True WDR, BLC, HLC |
| Electronic Shutter Speed | 1 sec. - 1/100000 sec. |
| DNR | 3D DNR |
| Angle Adjustments | Pan (0° - 345°), Tilt (0° - 77°), Rotation (0° - 345°) |

Network Specifications

| | |
|--------------|--|
| Protocols | UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, 802.1x, UPnP, HTTP, HTTPS, QoS |
| DDNS support | Speco DDNS (free of charge) |
| Security | User ID & Password protection, IP/MAC address filtering, digest authentication |
| User Access | Max. 3 simultaneous users (Actual number of users may vary depending on bandwidth) |

Video Specifications

| | |
|--------------------|--|
| Main Resolution | 8MP/ (1 - 20fps) 6MP/5MP/4MP/2K/3MP/2MP/720p (1-30fps) |
| Sub Stream | 20P(1-12fps)/D1/480 x 240(1-30fps) |
| Third Stream | D1/CIF/480 x 240 (1-30fps) |
| Compression | H.265, H.264 |
| Image Settings | Region of interest, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Defog, Sharpen, Noise Reduction, Corridor mode |
| Bitrate Control | VBR, CBR (64Kbps - 12Mbps) |
| Multiple Streaming | 3 streams |

Audio Specifications

| | |
|-------------|-----------------|
| Audio Codec | G.711A / G.711U |
|-------------|-----------------|

Interfaces

| | |
|--------------|-------------------------------------|
| Network | RJ45 jack |
| Power | DC jack |
| Audio input | Built-in mic, 3.5mm input |
| Audio output | 3.5mm out |
| Card Slot | MicroSD, up to 256GB (not included) |
| Alarm | 1 ch in/1ch out |
| Video out | CVBS |
| Reset | Yes |

Client Specifications

| | |
|---------------------|---|
| Web Browser Support | Chrome, Edge, Safari, Firefox |
| PC Application | SecureGuard® VMS, SecureGuard® CMS |
| Mobile | SecureGuard® App, Speco Blue (iPhone® and Android™) |

System Specifications

| | |
|-------------------|---|
| PoE | Standard (IEEE 802.3af) |
| Analytics | Motion, Exception, Line Crossing, Region Intrusion and video blurring detection |
| Alarm Triggers | Motion, Analytics, SD card error |
| Security Settings | Watermark, IP address filtering, video mask, password protection |

Operating & Unit Specifications

| | |
|-----------------------|---|
| Power | PoE, 12VDC (power supply not included) |
| Power Consumption | <10.5W |
| Operating Temperature | 40°F - 140°F (40°C - 60°C) |
| Operating Humidity | Less than 95 % (non-condensing) |
| Unit Dimensions | 5.55" (W) x 3.94" (H); 119mm (D); 141 x 100.2 |
| Unit Weight | 2.0 lb (0.91kg) |
| Certifications | FCC, RoHS |

*with compatible Speco recorder
**Products are in compliance with NDAA Section 889 Part B Guidelines

Optional Accessories



Cameras Interfaces

