

# 32CH 8K LumiSearch NVR – 32 Port

R54-32PA



## Key Features

- 8K NVR
- 32 Channels With Four (4) SATA Ports and One (1) eSATA Port
- 24 PoE Ports With LumiPower Support (Ports 1–8)
- HDMI/VGA Output
- Supports LumiSearch and LumiSearch+
- iMD, Face Recognition, and VCA by Recorder

## Certifications and Compliance

- NDAA Compliant
- FCC

## Learn More



Learn more about this product's key technologies.

## Overview

The **R54-32PA** is part of Luminys's R5 series. R5 series devices are designed with a suite of advanced LumiTechnologies to meet the needs of today's evolving security market.

## Key Technologies

### LumiSearch

LumiSearch lets you quickly find, track, and identify targets in security footage using a reference image. The LumiSearch algorithm analyzes human body shape, clothing color, and other characteristics to accurately pinpoint where a target has appeared in footage captured by any LumiSearch-enabled camera and NVR. All R5 series NVRs support LumiSearch and LumiSearch+.

### LumiPower

LumiPower technology enables long-distance Power over Ethernet transmission, extending power and data delivery up to 3,000 feet. This simplifies installations in larger or more complex environments by eliminating the need for additional power sources or repeaters. LumiPower ensures consistent connectivity and dependable power management, ideal for expansive security infrastructures.

### LumiViewer

LumiViewer is a desktop and mobile application that streamlines security management by providing real-time surveillance, playback of historical footage, and instant alarm notifications. With features like device sharing, an alarm hub for safety alerts, visual intercom for video calls and door control, and remote access management, LumiViewer ensures comprehensive and efficient monitoring.

# Specifications

## Video

Video Input	32 Channels
Recording Resolutions	32MP, 16MP, 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080p, 720p, D1, VGA, CIF
Output Resolutions	<b>HDMI (2CH):</b> 4K (3840 × 2160), 1920 × 1080, 1280 × 1024 <b>VGA (2CH):</b> 1920 × 1080, 1280 × 1024 HDMI1/HDMI2 Independent Output HDMI1/VGA1 Simultaneous Output HDMI2/VGA2 Simultaneous Output
Live View/Playback Resolutions	32MP, 16MP, 12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080p, 720p, D1, VGA, CIF

## Decoding

Format	H.265, H.264, H.264H, H.264B, MJPEG
Capability	<b>AI On</b> <ul style="list-style-type: none"><li>• 1CH at 32MP (30 fps)</li><li>• 2CH at 16MP (30 fps)</li><li>• 4CH at 8MP (30 fps)</li><li>• 12CH at 4MP (30 fps)</li><li>• 24CH at 1080p (30 fps)</li></ul> <b>AI Off</b> <ul style="list-style-type: none"><li>• 2CH at 32MP (30 fps)</li><li>• 4CH at 16MP (30 fps)</li><li>• 8CH at 8MP (30 fps)</li><li>• 16CH at 4MP (30 fps)</li><li>• 32CH at 1080p (30 fps)</li></ul>
Live View Window Division	1, 4, 9, 16, 25, 36 Views
Auxiliary Port Window Division	1, 4, 8, 9, 16 Views
Synchronous Playback	16 Channels

## Supported Analytics

Intelligent Motion Detection	Camera: 16CH NVR: 8CH
Video Content Analytics (VCA)	Camera: 16CH NVR: 4CH 10 Rules per Channel
Face Recognition	<b>Face Capture and Recognition: 2CH</b> <b>Face Picture Comparison Alarm From Camera: 16CH</b> Up to 20 Face Picture Libraries (Max. 20,000 Pictures Total)
LumiSearch	16CH (Must be Supported by Camera)
Video Metadata	8CH (Analytics by Camera)
License Plate Recognition	8CH (LPR Camera Required) Two (2) Block List, Two (2) Allow List Up to 20,000 Plate Numbers

## Interface

SATA	Four (4) Ports
eSATA	One (1) Port
HDD	Up to 16TB per HDD
Network	One (1) RJ-45 Self-Adaptive Ethernet (10/100/1000 Mbps)
PoE	24 x RJ-45 Self-Adaptive Ethernet (10/100 Mbps)
USB	<b>Front Panel:</b> 1 x USB 2.0 <b>Rear Panel:</b> 2 x USB 3.0
Serial Port	1 x RS-232
Alarm	<b>Input:</b> 16 Channels <b>Output:</b> 6 Channels
Audio	<b>Input:</b> 1-Channel RCA Input <b>Output:</b> 2-Channel RCA Output

## Network

Bandwidth	<b>AI On</b> <ul style="list-style-type: none"><li>• <b>Incoming:</b> 220 Mbps</li><li>• <b>Outgoing:</b> 220 Mbps</li></ul> <b>AI Off</b> <ul style="list-style-type: none"><li>• <b>Incoming:</b> 400 Mbps</li><li>• <b>Outgoing:</b> 400 Mbps</li></ul>
Protocol	HTTP, HTTPS, TCP/IP, IPv4, IPv6, UPnP, SNMP, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS
Interoperability	ONVIF, RTSP
PoE Standard	IEEE 802.3 af/at
Client	LumiViewer, LumiViewer Mobile App

## Electrical

Power Supply	100 to 240 VAC, 50 to 60 Hz
Power Consumption	< 13 W (HDD Not Included) <b>PoE:</b> 210 W(Max. Output for Single Port: 25.5 W)

## Construction

Installation Method	Rack- or Desktop-Mount
Weight	4.7 kg (10.4 lb) Without HDD
Operating Temperature	-10 °C to 55 °C (14 °F to 131 °F) 10% to 93%
Dimensions (W × D × H)	442.0 × 414.1 × 68.0 mm (17.4 × 16.3 × 2.7 in.)

## Certifications and Compliance

Certifications	FCC
Compliance	NDAA