


Card Enrollment Reader

R-ECA



Key Features

- Read and Issue MIFARE (IC) Cards
- USB 2.0 Port
- Plug-and-Play
- Indicator Light

Certifications and Compliance

- NDAA Compliant
- FCC

Learn More



Learn more about this product's key technologies.



View all compatible accessories for this product.

Overview

The **R-ECA** is part of Luminys's access control product range. Luminys access control solutions are built for flexibility and scalability and provide reliable, secure access for applications of all sizes.

Key Technologies

USB integration allows for seamless credential enrollment, streamlining management with plug-and-play USB connectivity.

Specifications

System

Card Reading Frequency	13.56 MHz
Card Issuing Distance	1.2 in. to 2.0 in. (3.0 cm to 5.0 cm)
Supported Card Type	IC Card (MIFARE card)
Status Indicator Light	<ul style="list-style-type: none">• Solid Red: Abnormal Operation or Failed to Issue Card• Solid Green: Operation Normal or Card Issued Successfully
Buzzer	Built-In

Electrical

Power Supply	5 VDC, 0.5 A
Power Consumption	<ul style="list-style-type: none">• Standby: ≤ 1.0 W• Working: ≤ 1.7 W

Construction

Gross Weight	0.2 kg (0.4 lb)
Product Dimensions	4.1 in. x 3.0 in. x 0.8 in. (105.0 mm x 75.0 mm x 20.0 mm)
Package Dimensions	7.6 in. x 5.2 in. x 2.1 in. (192.0 mm x 132.0 mm x 54.0 mm)
Operating Temperature	-22 °F to 140 °F (-30 °C to 60 °C) 5% to 95% (RH), Non-Condensing
Material	PC and ABS

Certifications and Compliance

Certifications	FCC
----------------	-----